

#### MATERIAL SAFETY DATA SHEET

## MSDS# 2652

#### SECTION 1

QUADRANT EPP 2120 FAIRMONT AVENUE P.O. BOX 14235 READING, PA. 19612-4235 TELEPHONE NUMBERS:

PRODUCT INFORMATION (QUADRANT EPP ) 610-320-6600

TRANSPORTATION EMERGENCY (CHEMTREC) 800-424-9300

## MATERIAL IDENTIFICATION

PRODUCT NAME: DURATRON 150

CHEMICAL NAME: AROMATIC POLYIMIDE POLYMER.

CAS NO.: 58698-66-1 (BASE RESIN)

PRODUCT USE: ENGINEERING POLYMER SHAPE FOR SUBSEQUENT

FABRICATION.

TSCA INVENTORY STATUS: ALL REPORTABLE INGREDIENTS ARE LISTED IN

THE TSCA CHEMICAL SUBSTANCE INVENTORY.

## SECTION 2

HAZARDOUS INGREDIENTS (ADDITIVES NOT HAZARDOUS BY 29CFR 1910.1200)

IDENTITY CAS# CONCENTRATION TVL (ACGIH)

NATURAL GRAPHITE
AIROMATIC POLYIMIDE

CAS# CONCENTRATION TVL (ACGIH)

58698-66-1

5-15%

2.0 MG/M³

\_\_\_\_\_

## SECTION 3

## HEALTH HAZARD DATA

ACUTE OR IMMEDIATE EFFECTS: ROUTES OF ENTRY AND SYSTEMS.

INGESTION: NOT A PROBABLE ROUTE OF EXPOSURE.

SKIN: MOLTEN POLYMER CAUSES THERMAL BURNS.

EYE: MECHANICAL IRRITATION ONLY.

INHALATION: SHAPES NOT RESPIRABLE BUT MACHINING MAY GENERATE A NUISANCE DUST WHICH CAN CAUSE MECHANICAL IRRITATION TO THE EYES, SKIN, NOSE AND THROAT.

## Page 2

#### EMERGENCY FIRST AID

- IF EXPOSED TO FUMES FROM OVERHEATING, MOVE TO FRESH AIR. CONSULT A PHYSICIAN IF SYMPTOMS PERSIST.
- WASH SKIN WITH SOAP AND PLENTY OF WATER.
- FLUSH EYES WITH WATER. CONSULT A PHYSICIAN IF SYMPTOMS PERSIST.
- IF MOLTEN POLYMER CONTACTS SKIN, COOL RAPIDLY WITH COLD WATER. DO NOT ATTEMPT TO PEEL POLYMER FROM SKIN. OBTAIN MEDICAL ATTENTION TO THERMAL BURN.

CHRONIC EFFECTS: NONE KNOWN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY THIS MATERIAL: NONE KNOWN.

SECTION 5

#### FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: NO OBSERVED FLASHPOINT

USUAL FIRE, EXPLOSION HAZARDS: TOXIC FUMES MAY BE EMITTED AT EXTREME TEMPERATURES.

HAZARDOUS DECOMBUSTION PRODUCTS: CO, TRACES OF HCN, NOx, NH3.

SPECIAL FIRE FIGHTING INSTRUCTIONS: FIRE FIGHTERS AND OTHERS EXPOSED TO PRODUCTS OF COMBUSTION SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF-CONTAINED BREATHING APPARATUS. FIRE FIGHTING EOUIPMENT SHOULD BE THOROUGHLY DECONTAMINATED AFTER USE.

EXTINGUISHING MEDIA: WATER SPRAY OR ANY CLASS A EXTINGUISHING AGENT.

EXTINGUISHING MEDIA TO BE AVOIDED: HALONE, DRY CHEMICAL (NOT ENOUGH COOLING EFFECT)

#### PHYSICAL HEALTH HAZARDS:

DUST MAY FORM EXPLOSIVE MIXTURES WITH AIR. AVOID DUST FORMATION AND CONTROL IGNITION SOURCES. ALL PLASTIC DUST PARTICLES SUSPENDED IN AIR ARE COMBUSTIBLE AND MAY BE EXPLOSIVE. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND OTHER IGNITION SOURCES. PREVENT DUST ACCUMULATIONS AND DUST CLOUDS. EMPLOY GROUNDING, VENTING, AND EXPLOSIVE RELIEF PROVISIONS IN ACCORDANCE WITH ACCEPTED ENGINEERING PRACTICES AND NFPA PROVISIONS IN ANY PROCESS CAPABLE OF GENERATING DUST AND/OR STATIC ELECTRICITY. EXPLOSION HAZARDS APPLY ONLY TO DUSTS, NOT GRANULAR FORMS OF THIS PRODUCT. SEE ALSO SPECIAL PRECAUTIONS SECTION BELOW.

## ACCIDENTAL RELEASES

SPILL OR RELEASE: CLEAN UP BY VACUUMING OR SWEEPING TO PREVENT FALLS.

#### SECTION 7

## STORAGE CONDITIONS

DRY STORAGE. KEEP CONTAINERS CLOSED TO PREVENT CONTAMINATION.

\_\_\_\_\_\_

#### SECTION 8

## PROTECTION INFORMATION

EYE: SAFETY GLASSES ARE RECOMMENDED TO PREVENT PARTICULATE MATTER FROM ENTERING EYES WHILE GRINDING OR MACHINING.

SKIN: PROTECTIVE GLOVES ARE REQUIRED WHEN HANDLING HOT POLYMER. ALSO, LONG SLEEVE COTTON SHIRT AND LONG PANTS IF HANDLING MOLTEN POLYMER.

VENTILATION: LOCAL EXHAUST AT PROCESSING EQUIPMENT TO KEEP PARTICULATES BELOW 5 MG/M3, THE OSHA LIMIT FOR RESPIRABLE DUSTS. GRINDING AND MACHINING OF PARTS SHOULD BE REVIEWED TO ASSURE THAT PARTICULATE LEVELS ARE KEPT AT RECOMMENDED LEVELS.

RESPIRATOR: IF DUST IS GENERATED AND VENTILATION IS INADEQUATE, USE NIOSH/MSHA CERTIFIED RESPIRATOR, WHICH WILL PROTECT AGAINST DUST.

## PHYSICAL/CHEMICAL DATA

APPEARANCE: DARK GRAY COLOR. SHAPE MAY BE IN THE FORM OF

DISC, PLATE OR TUBE

ODOR: ESSENTIALLY ODORLESS.

MELTING POINT: N/A

SOLUBILITY IN WATER: INSOLUBLE.

VOLATILE CONTENT %: <1%

SPECIFIC GRAVITY: 1.38

PRECAUTIONS FOR REPAIR & MAINTENANCE OF CONTAMINATED EQUIPMENT: ELIMINATE IGNITION SOURCES:

TRANSFER FROM STORAGE WITH A MINIMUM AMOUNT OF DUSTING.
GROUND ALL TRANSFER, BLENDING, AND DUST COLLECTING EQUIPMENT
TO PREVENT STATIC SPARKS IN ACCORDANCE WITH NFPA 70 "NATIONAL
ELECTRIC CODE". REVIEW AND COMPLY WITH ALL RELEVANT NFPA
PROVISIONS, INCLUDING BUT NOT LIMITED TO NFPA 484 AND NFPA 654
RELATED TO COMBUSTIBLE DUST HAZARDS. REMOVE ALL IGNITION
SOURCES FROM MATERIAL HANDLING, TRANSFER, AND PROCESSING AREAS
WHERE DUST MAY BE PRESENT. LOCAL EXHAUST VENTILATION SHOULD
BE PROVIDED IN WORK AREA.

#### SECTION 10

#### HAZARDOUS REACTIVITY

STABILITY: STABLE UNDER NORMAL CONDITIONS
CONDITIONS TO AVOID: LONG-TERM EXPOSURE TO ALKALINE MEDIA.
MATERIALS TO AVOID: REACTS WITH MOLTEN ALKALI METALS AND
FINELY DIVIDED MAGNESIUM AND ALUMINUM AT TEMPERATURES ABOVE
425°C (797°F).

HAZARDOUS POLYMERIZATION: N/A

HAZARDOUS DECOMPOSITION PRODUCTS: **DECOMPOSITION OCCURS AT TEMPERATURES NEAR 425°C (842°F). CARBON MONOXIDE, TRACES OF ANILINE, HYDROGEN CYANIDE, AND NO.** 

\_\_\_\_\_

## TOXICOLOGICAL INFORMATION

CHRONIC TOXICITY: DURATRON 150 DOES NOT APPEAR TO POSSESS ANY TOXICOLOGICAL PROPERTIES.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: NONE KNOWN.

CARCINOGENICITY: NONE KNOWN.

#### SECTION 12

## ECOLOGICAL INFORMATION

AQUATIC TOXICITY: TOXICITY IS EXPECTED TO BE LOW BASED ON INSOLUBILITY OF POLYMER IN WATER.

\_\_\_\_\_

## SECTION 13

## DISPOSAL

SPILL OR RELEASE: CLEAN UP BY VACUUMING OR WET SWEEPING TO MINIMIZE DUST EXPOSURE.

WASTE DISPOSAL: RECYCLING IS ENCOURAGED, LANDFILL OR INCINERATION IN COMPLIANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

### SECTION 14

## TRANSPORT INFORMATION

DOT HAZARD CLASS: **NA** SHIPPING NAME: **NA** 

# SECTION 15A REGULATORY INFORMATION

SECTION 313 SUPPLIER NOTIFICATION (SARA TITLE III-TOXIC CHEMICALS LIST)

THIS PRODUCT CONTAINS NO KNOWN TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND 40 CFR 372.

## STATE RIGHT TO KNOW LAWS

NO SUBSTANCES ON THE STATE HAZARDOUS LIST, FOR THE STATES INDICATED BELOW, ARE USED IN THE MANUFACTURE OF PRODUCTS ON THIS MATERIAL SAFETY DATA SHEET, WITH THE EXCEPTIONS INDICATED. WHILE WE DO NOT SPECIFICALLY ANALYZE THESE PRODUCTS, OR THE RAW MATERIALS USED IN THEIR MANUFACTURE, FOR SUBSTANCES ON VARIOUS STATE HAZARDOUS SUBSTANCES LISTS, TO THE BEST OF OUR KNOWLEDGE THE PRODUCTS ON THIS MATERIAL SAFETY DATA SHEET CONTAIN NO SUCH SUBSTANCES EXCEPT FOR THOSE SPECIFICALLY LISTED BELOW:

## PENNSYLVANIA:

SUBSTANCES ON THE PENNSYLVANIA HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 1% OR MORE: NONE KNOWN.

SUBSTANCES ON THE PENNSYLVANIA SPECIAL HAZARDOUS SUBSTANCES LIST PRESENT AT A CONCENTRATION OF 0.01% OR MORE: NONE KNOWN.

## CALIFORNIA PROPOSITION 65:

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: NONE KNOWN.

SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: NONE KNOWN.

## SECTION 15B LABELING INFORMATION

HEALTH	0
FLAMMABILITY	1
REACTIVITY	0
PPE	A
#ACUTE	
*CHRONIC	

## MISCELLANEOUS INFORMATION

Reviewed by: Michael Yohn

Issued: 18-October-2012

Supersedes: 01-March-2012

The information set forth herein has been gathered from standard reference materials and/or supplier test data and is, to the best knowledge and belief of Quadrant EPP, accurate and reliable. Such information is offered solely for your consideration, investigation and verification, and it is not suggested or guaranteed that the hazard precautions or procedures mentioned are the only ones, which exist. Quadrant EPP makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein in combination with any other material or process, and assumes no responsibility therefor.

NA = Not

NE = Not established.

> = New or revised information in this section when " > " appears in the left margin.

END OF MSDS