

Product Data Sheet

Product : Quadrant Polypenco Korea PCGF, Polycarbonate included 20% glass fiber, Unfilled, extruded

Categories : Polymer; Thermoplastic; Polycarbonate including 20% glass fiber

Material Notes : PCGF stock shapes are produced from selected batches of a specific UV-stabilized polycarbonate resin. This polymer shows a combination of good mechanical, thermal and electrical properties combined with a good chemical resistance.

Properties	Units	Test Methods	PCGF
Physical Properties			
Specific Gravity	g/cc	ASTM D 792	1.34
Water Absorption, Immersion, 24hr	%	ASTM D 570(2)	0.15
Water Absorption at Saturation, Immersion	%	ASTM D 570(2)	0.32
Mechanical Properties			
Rockwell Hardness, M	M scale	ASTM D 785	-
Rockwell Hardness, R	R scale	ASTM D 785	122
Hardness, Shore D	D	ASTM D 2240	-
Tensile Strength	MPa	ASTM D 638	97.0
Tensile Modulus	GPa	ASTM D 638	4.79
Elongation at Break	%	ASTM D 638	3.0
Flexural Yield Strength	MPa	ASTM D 790	104
Flexural Modulus	GPa	ASTM D 790	3.97
Compressive Strength	MPa	10% Def.; ASTM D 695	-
Compressive Modulus	GPa	ASTM D 695	-
Shear Strength	MPa	ASTM D 732	-
Coefficient of Friction; Dry vs. Steel	-	QTM 55007	-
K (wear) Factor	mm ³ /N-M	QTM 55010	-
Limiting Pressure Velocity; 4:1 safety factor	MPa-m/sec	QTM 55007	-
Izod Impact, Notched	J/m	ASTM D 256	122
Electrical Properties			
Surface Resistivity per Square	Ω	EOS/ESD S11.11	-
Dielectric Constant	-	ASTM D 150	- @Frequency 1e+6 Hz
Dielectric Strength; Short term	kV/mm	ASTM D 149	-

Dissipation Factor	-	ASTM D 150	@Frequency 1e+6 Hz
--------------------	---	------------	--------------------

Thermal Properties

Coefficient of Thermal Expansion; CTE, linear	µm/m-°C	ASTM E 831	- @Temperature -40.0 - 149 °C
Thermal Conductivity	W/m-K	ASTM F 433	-
Melting point ; Crystalline, Peak	°C	ASTM D 3418	-
Maximum Service Temperature, Air	°C	Long Term	-
Deflection Temperature at 1.8 Mpa (264psi)	°C	ASTM D 648	-
Glass Transition Temp, Tg		ASTM D 3418	-
Flammability, UL94 ; 1/8inch(Estimated Rating)	-	-	HB

Compliance Property

Comments

3A-Dairy	No
Canada AG	No
FDA	No
NSF	No
USDA	No
RoHS	Yes

Descriptive Properties

Color	Natural / Black
Machinability	1-10, 1=Easier to Machine
	3

Chemical Resistance Properties

Acid, Strong (pH1-3)	Unacceptable
Acids, Weak	Acceptable
Alcohls	Acceptable
Alkalies, Weak	Unacceptable
Alkalies, Strong (pH 11-14)	Acceptable
Chlorinated Solvent	Unacceptable
Conductive / Static Dissipative	No
Continuous Sunlight	Limited
Hot Water / Steam	Limited
Hydrocarbons – Aliphatic	Limited
Hydrocarbons – Aromatic	Unacceptable
Inorganic Salt Solution	Acceptable

Ketones, Esters

Unacceptable

Miscellaneous Properties

Targeted Usage

Structural Uses

All information supplied by or on behalf of Polypenco Korea in relation to its products, in any form, is supported by research and believed to be reliable, but Polypenco Korea assumes no liability whatsoever in respect of application, processing or use made of the aforementioned information or products, or any consequence thereof. The buyer undertakes all liability in respect of the application, processing or use of the aforementioned information or product, whose quality and other properties he shall verify, or any consequence thereof. No liability whatsoever shall attach to Polypenco Korea for any infringement of the rights owned or controlled by a third party in intellectual, industrial or other property by reason of the application, processing or use of the aforementioned information or products by the buyer.